## **DBNI-60** Mid-Duty Squeeze Tool 6" IPS Hydraulic ML Series

The Model DBM-60 Medium Duty Squeeze Tool is similar to the DBG-60 manual tool with the exception that it is hydraulically operated.

A reduced-stroke version of Mustang's proven hydraulic cylinder provides 41,000lbs of force directly over the pipe. The cylinder incorporates a built in locking valve to assure that pressure is maintained on the pipe in the event of a hydraulic failure.

Saddle clamps are provided to mechanically lock the upper and lower jaws and to assist in accomplishing a good squeeze off.

Weight:117lbsDimensions:42" HeightCapacity:Specify (2) Sizes (see table below)

0

MUSTANG SQUEEZE TOOLS

DBM-60 Unit Includes: > Model 20 Hydraulic Pump > SC-60 Saddle Clamps

> Squeeze Release Control Valve (optional)



2401 Lockheed Way Carson City, NV 89706 775.883.0732 Tel 775.883.3372 Fax

**Pipe Size** 

IPS 3"

IPS 4"

IPS 6"

Nominal Wall

Thickness

.259

.307-.318

.389

.333

.395-.409

.500-.548

.427

.491

.568-.602

mustangmfg@gbis.com www.squeezetool.com

Gap

Stop

.450

.500

.675

.560

.675

.800

.725

.813

1.00

SDR

13.5

11.5-11

9

13.5

11.5-11

9

15.5

13.5

11.5-11

%Max

Squeeze 26

29

26

25

26

24

22

26

26